



## RUEDAS Y NEUMÁTICOS PARA REMOLQUES, CISTERNAS, ESPARCIDORES Y OTROS VEHÍCULOS ARRASTRADOS



Ø	Neumático**	Rueda	Ataque	Medidas en mm.		Índice Carga/vel.*	Presión (bars)	Peso (kgs.)
				ancho	diámetro			
17,5	215/75 R 17,5	6.75x17,5	6/ 161-205	215	767	135/133J	8	35
	225/75 R 17,5			225	783	129/127M		36
	235/75 R 17,5			235	797	143/141J		37
	245/70 R 17,5			245	813	143/141J		38
	245/70 R 19,5			8.25x19,5	6/ 161-205 y 8/ 221-275	245		839
19,5	265/70 R 19,5	265	867			143/141J	60	
	285/70 R 19,5	285	880			150/147J	70	
	305/70 R 19,5	305	910			148/145M	70	
19,5	385/55 R 19,5	11.75x19,5	8/ 221-275			385	920	160J
	435/50 R 19,5	14.00x19,5		435	931	160J	90	
	445/45 R 19,5	11.75x22,5		445	910	160J	90	
	22,5			385/55 R 22,5	385	996	160K	100
385/65 R 22,5		14.00x22.5"	8/ 221-275	385	1072	160K	110	
445/65 R 22,5			y 10/281-335	445	1150	168K	9	120

\* Ver tabla de índices de carga y velocidad.

\*\* Disponibles mismas medidas de neumáticos vulcanizados en carcasa de camión.