

RUEDAS Y NEUMÁTICOS FLOTACIÓN Y TRACCIÓN



Fig.1



Fig.2



Fig.3



Código	Neumático	Dibujo	Rueda	Desplaz.	Ataque	Medidas en mm.		Índice Carga/vel. *	Presión (bars)	Peso (kgs.)
						ancho	diámetro			
CJT12"002	10/80-12" 10PR	Fig.1	7.00-12"	0	5/ 94-140	260	710	120A8	3	20
CJT15,3"005	10.0/75-15,3" 10PR		9.00-15.3"			270	750	123A8	4	33
CJT15,3"006	10.0/75-15,3" 12PR					126A8	4,75	34		
CJT15,3"007	10.0/75-15,3" 14PR		130A8			5,5	35			
CJT15,3"001	10.0/75-15,3" 18PR		9.00-15.3" REF.			143A8	7	39		
CJT15,3"002	11.5/80-15,3" 10PR		9.00-15.3"			290	850	131A8	3,5	36
CJT15,3"008	11.5/80-15,3" 12PR					134A8	4	37		
CJT15,3"004	11.5/80-15,3" 14PR					139A8	4,75	39		
CJT15,3"003	11.5/80-15,3" 16PR					142A8	5,5	42		
CJT15,5"002	400/60 15.5" 14PR		Fig.2			13.00-15.5"	8/ 221-275	405	875	145A8
CJT15,5"001	400/60 15.5" 14PR	400		875	145A8	3,5		62		
CJT22.5"011	550/60 22,5" 16PR	Fig.3		16.00X22.5"	537	1254		163A8	2,8	110
CJT22.5"012	560/60R 22,5" 161D				564	1244		161D	4	115

*Ver tabla Índices de carga y velocidad