

RUEDAS Y NEUMÁTICOS DE USO INDUSTRIAL



Código	Neumático	Rueda	Desplaz.	Ataque	Medidas en mm.		Capacidad de carga a 25 km/h	Presión (bars)	Peso (kgs.)
					ancho	diámetro			
CJT08"008	4.00 - 8" 8PR	3.00D-8"	0	5/ 94-140	112	414	750	8	7,5
CJT08"009	5.00- 8" 10PR	4.33R-8"	AC y AG		135	470	1000	8	9
CJT08"005	18X7 -8" 14PR				4.00E-9"	173	462	1450	9
-	6.00-9" 12PR	4.00E-9"	AC y AG	160	540	1500	10	17	
-	6.50-10" 10PR	5.50F-10"	0	177	588	1500	8	27	
CJT10"001	7.00-12" 14PR	5.00S-12"	AC y AG	6/ 161-205	190	675	2125	9	40
-	7.00-12" 14PR	5.00S-12"			190	675	2125		
-	7.50-15 16PR	6.0S-15"			217	772	3400		
-	8.15-15" 14PR	6,50-15"			215	715	3000	10	50
-	8.25-15" 14PR				240	835	3300	8	56



RUEDAS Y MACIZOS SUPERELÁSTICOS.

Código	Macizo	Rueda	Ataque	Medidas en mm.		capacidad carga a 25 km/h	Peso (kgs.)
				ancho	diámetro		
CJT08"010	MCZ 4.00 - 8"	3.00D-8"	5/ 94-140	130	406	730	17
CJT08"011	MCZ 15x41/2 - 8"		4/ 58-98	132	377	800	17
CJT08"012	MCZ 15x41/2 - 8"		132	377	800	17	
CJT08"013	MCZ 5.00 - 8"	4.33R-8"	5/ 94-140	143	458	1090	20
CJT08"007	MCZ 18X7.8 - 8"			187	453	1650	26
CJT09"003	MCZ. 6.00 - 9"	4.00E-9"	173	629	1450	32	
CJT12"012	MCZ 7.00 - 12"	5.00S-12"	207	657	2240	40	
CJT12"004	MCZ 7.00 - 12"	5.00S-12"	207	657	2240	40	
CJT15"005	MCZ 7.50 - 15"	6,50-15"	6/ 161-205	229	757	3000	-
CJT12"006	MCZ. 8.25 - 15"	253	819	3540	-		

RUEDAS Y MACIZOS SUPERELÁSTICOS LISOS PARA PLATAFORMAS.

Código	Macizo	Rueda	Ataque	Medidas en mm.		capacidad carga a 25 km/h	Peso (kgs.)
				ancho	diámetro		
CJT08"014	MCZ 12x31/2 - 8"	3.00D-8"	5/ 94-140	100	300	815	10
CJT08"015	MCZ 15x41/2 - 8"		4/ 58-98	132	377	1050	17
CJT08"016	MCZ 15x41/2 - 8"		132	377	1050	17	
CJT08"017	MCZ 17x7 - 8"	4.33R-8"	5/ 94-140	150	430	1400	22